

SRB202CS/T-24VDC



- 2 Signalling outputs
- Two-functions safety monitoring module (double evaluation)
- Level 1: Reset with edge detection, Level 2 Opener (NC) / Opener (NC)
- 2 enabling paths with different shut-down behaviour, e.g. emergency exit opens both enabling paths (level 1); guard door monitoring only opens the second enabling path (level 2)
- Suitable for signal processing of potential-free contacts, e.g. Emergency Stop command devices (level 1), position switches with safety function, solenoid interlocks and safety sensors (level 2)

Data

Ordering data

Product type description	SRB202CS/T 24VDC
Article number (order number)	101176210
EAN (European Article Number)	4250116201907
eCl@ss number, Version 9.0	27-37-18-19
Replacement article number	101177155

Certifications

Certificates	cULus EAC
--------------	--------------

General data

Product name	SRB202CS
--------------	----------

Standards	IEC 61508
	IEC/EN 60204-1
	ISO 13849-1
	EN 60947-5-1
Climatic stress	EN 60068-2-78
Enclosure material	Glass-fibre reinforced thermoplastic, ventilated
Material of the contacts, electrical	Ag-Ni, self-cleaning, positive drive
Gross weight	235 g

General data - Features

Stop-Category	0
Electronic Fuse	Yes
Wire breakage detection	Yes
Removable Terminals	Yes
Start input	Yes
Feedback circuit	Yes
Automatic reset function	Yes
Reset edge detection	Yes
Earth connection detection	Yes
Integral System Diagnostics, status	Yes
Number of auxiliary contacts	2
Number of inputs for NC	2
Number of inputs for NO	2
Number of LEDs	6
Number of safety contacts	2

Safety appraisal

Standards	EN 60947-5-1
	IEC 61508

Safety appraisal - Relay outputs

Performance Level, Stop 0	e
Category, Stop 0	4
Diagnostic Coverage (DC) Level, Stop 0	$\geq 99 \%$
PFH-Value Stop 0	$2.00 \times 10^{-8} /h$
Safety Integrity Level (SIL), Stop 0	3

Mechanical data

Mounting	Snaps onto standard DIN rail to EN 60715
Mechanical life, minimum	10,000,000 Operations

Mechanical data - Connection technique

Terminal Connector	Screw connection rigid or flexible
Terminal designations	IEC/EN 60947-1
Cable section, minimum	0.25 mm ²
Cable section, maximum	2.5 mm ²
Tightening torque of Clips	0.6 Nm

Mechanical data - Dimensions

Width	22.5 mm
Height	100 mm
Depth	121 mm

Ambient conditions

Protection class of the enclosure	IP40
Protection class of the Clearance	IP54
Protection class of Clips or Terminals	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+45 °C
Storage and transport temperature, minimum	-40 °C
Storage and transport temperature, maximum	+85 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, Amplitude 0.35 mm
Resistance to shock	10 g / 11 ms

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
	III

Degree of pollution to IEC/EN 60664-1 2

Electrical data

Rated operating voltage	24 VDC -15%/+20%, residual ripple max. 10%
Rated AC voltage for controls at DC minimum	20.4 VDC
Rated control voltage at DC, maximum	28.8 VDC
Electrical power consumption	4.4 W
Contact resistance, maximum	0.1 Ω
Note (Contact resistance)	in new state
Drop-out delay in case of power failure, typically	80 ms
Drop-out delay in case of emergency, typically	20 ms
Pull-in delay at automatic start, maximum, typically	100 ms
Pull-in delay at automatic start	Adjustable
Pull-in delay at RESET, typically	20 ms

Electrical data - Safe relay outputs

Switching capacity, minimum	10 VDC
Switching capacity, minimum	10 mA
Switching capacity, maximum	250 VAC
Switching capacity, maximum	8 A

Electrical data - Digital inputs

Conduction resistance, maximum	40 Ω
--------------------------------	-------------

Electrical data - Relay outputs (auxiliary contacts)

Switching capacity, maximum	24 VDC
-----------------------------	--------

Switching capacity,
maximum

2 A

Electrical data - Electromagnetic compatibility (EMC)

EMC-Directive

Status indication

Indicated operating
states

Position relay K2
Position relay K1
Internal operating voltage U_i
Position relay K3

Other data

Note (applications)

Safety sensor
Guard system
Pull-wire emergency stop switches
Emergency stop button

Notes

Note (General)

Inductive loads (e.g. contactors, relays, etc.) are to be suppressed by means of a suitable circuit.

Note (Short-circuit
recognition)

Level 1

Circuit example

Note (Wiring diagram)

The wiring diagram is shown with guard doors closed and in de-energised condition. Relay outputs: Suitable for 2 channel control, for increase in capacity or number of contacts by means of contactors or relays with positive-guided contacts. The control recognises cross-short, cable break and earth leakages in the monitoring circuit.

Input level: the example shows a 2-channel control of an Emergency Stop command device (level 1) with external reset button (R), and guard door monitoring (level 2) with feedback circuit (H2).

Automatic start (level 1): The automatic start is programmed by connecting the feedback circuit to the terminals X1/+24 V DC. Automatic start (level 2): The automatic start is programmed by connecting the feedback circuit to the terminals X2/+24 V DC. If the feedback circuit is not required, establish a bridge.

1 NC contact each time communicates the status of level 1 and level 2

Pictures

Product picture (catalogue individual photo)



ID: ksrb2f04

| 169,5 kB | .jpg | 27.093 x 63.669 mm - 320 x 752

Pixel - 300 dpi


| 100,7 kB | .png | 74.083 x 173.919 mm - 210 x 493

Pixel - 72 dpi

| 808,9 kB | .jpg | 265.994 x 625.122 mm - 754 x 1772

Pixel - 72 dpi

Wiring example




ID: 1srb2l06

| 108,8 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703

Pixel - 72 dpi

| 31,0 kB | .cdr |

Wiring example



ID: ksrb2l06

| 53,2 kB | .cdr |

| 159,4 kB | .jpg | 352.778 x 291.394 mm - 1000 x 826

Pixel - 72 dpi

Symbol (technical standard)

K	n-op/y	t-cycle
20 %	525.600	1,0 min
40 %	210.240	2,5 min
60 %	75.087	7,0 min
80 %	30.918	17,0 min
100 %	12.223	43,0 min

ID: kformm02

| 191,1 kB | .jpg | 352.778 x 246.592 mm - 1000 x 699

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 20.05.2020 15:22:46