



Terminal block, 1 pole, 400A, 11 output terminals

Part no. BPZ-KB-11/400
102713
EL Number 2459289
(Norway)

General specifications		
Product name		Eaton xEnergy Basic other accessory
Part no.		BPZ-KB-11/400
EAN		4015081025732
Product Length/Depth		49 millimetre
Product height		95.4 millimetre
Product width		44.5 millimetre
Product weight		0.5 kilogram
Compliances		RoHS conform
Certifications		UL 1059 IEC 60 947 -7 -1
Product Tradename		xEnergy Basic
Product Type		Accessories
Product Sub Type		Other
Delivery program		
Amperage rating		400 A
Number of poles		Single-pole
Technical Data - Electrical		
Voltage rating at AC Cu (CSA) - max		600 V AC
Voltage rating at AC Cu (IEC) - max		1000 V AC
Voltage rating at AC Cu (UL) - max		600 V AC
Voltage rating at DC Cu (IEC) - max		1500 V DC
Rated peak withstand current		51 kA
Rated operation current (Ie) Cu (CSA)		310 A
Rated operation current (Ie) Cu (IEC)		400 A
Rated operation current (Ie) Cu (UL)		310 A
Rated short-time withstand current (Icw)		21 kA
Technical Data - Mechanical		
Mounting method		Flush mounting Floor standing distribution board Surface mounting
Mounting position		Universal
Degree of protection		IP10
Number of clamp positions per pole		12
Number of clamping units per pole		12
Terminal capacity (single/multi-wire)		2.5 mm ² - 25 mm ² (outgoing, fine wire (with sleeve)) 14 - 6 AWG (outgoing) 14 - 8 AWG (outgoing) 2.5 mm ² - 16 mm ² (outgoing) 14 - 8 AWG (outgoing, fine wire (with sleeve)) 95 mm ² - 185 mm ² (incoming) 3/0 - 5/0 AWG (incoming, fine wire (with sleeve)) 2.5 mm ² - 16 mm ² (outgoing, fine wire (with sleeve)) 14 - 4 AWG (outgoing, fine wire (with sleeve)) 2.5 mm ² -35 mm ² (outgoing) 3/0 - 350 MCM AWG (incoming) 14 - 6 AWG (outgoing, fine wire (with sleeve)) 2.5 mm ² - 10 mm ² (outgoing, fine wire (with sleeve)) 95 mm ² - 150 mm ² (incoming, fine wire (with sleeve)) 14 - 2 AWG (outgoing) 2.5 mm ² - 10 mm ² (outgoing)
Conductor cross section (solid, solid-strand) - min		1.5 mm ²
Conductor cross section (solid, solid-strand) - max		185 mm ²
Clamp material		Brass Plain

Torque rating			25 Nm / 221.2 lbf (incoming). 2 Nm - 7 Nm / 17 lbf - 62 lbf (outgoing)
Housing color			Light gray (RAL 7035)
Housing material			PA66
Design verification as per IEC/EN 61439 - technical data			
Heat deflection temperature			100 °C
Additional information			
Comparative tracking index (CTI)			600 V
Flame classification (UL 94)			V-0
Functions			Additional equipment
Special features			Zinc plated (Hexagon socket set screw, Surface finish) Material, hexagon socket set screw: Steel Modular construction, 1-4 pole Systems can be built with several blocks. Save 80% on space used. Save time on wiring. Clicks on DIN-rail or on base plate.

Technical data ETIM 9.0

Energy distribution systems (EG000015) / Distributor assembly terminal blocks (EC001894)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly terminal blocks (ecI@ss13-27-40-06-09 [AC0381016])			
Height		mm	95.4
Width		mm	44.5
Depth		mm	49
Max. rated current		A	400
Number of poles			1
Conductor cross section flexible (fine-strand) with cable end sleeve		mm²	1.5 - 185
Conductor cross section solid (solid, stranded)		mm²	1.5 - 185
Number of clamp positions per pole			12
With PE-rail			No
With N-rail			No